




## TUBES FROM ALUMINISED AND CALORISED MATERIAL TUBI ALUMINATI CALORIZZATI

Weight and availability table / *Pesi e gamma produttiva*

Ø OD Ø Esterno mm	OD Tolerances* Tolleranza	Theoretic weight kg / m - <i>Pesi teorici kg / m</i>	
		Nominal thickness mm / <i>Spessori nominali mm</i>	
		1,50	2,00
40,0		1,47	1,96
42,0		1,54	2,06
50,0		1,84	2,45
50,8		1,87	2,49
54,0		1,98	2,65
58,0		2,13	2,84
60,0		2,20	2,94
63,0		2,31	3,09
65,0		2,39	3,18
70,0		2,57	3,43
73,0		2,68	3,58
74,0		2,72	3,62
75,0		2,76	3,67
<b>76,2</b>		<b>2,80</b>	3,73
80,0		2,94	3,92
82,0		3,01	4,02
85,0		3,12	4,16
<b>88,9</b>		<b>3,27</b>	4,35
90,0		3,31	4,41
94,0		3,45	4,60
95,0		3,49	4,65
100,0		<b>3,67</b>	4,90
<b>101,6</b>		<b>3,73</b>	<b>4,98</b>
103,0		3,78	5,05
104,0		3,82	5,09
105,0		3,86	5,14
106,0	+/-0,5%	3,89	5,19
108,0		3,97	5,29
110,0		4,04	<b>5,39</b>
114,3		4,20	5,60
115,0		4,22	5,63
118,0		4,34	5,78
120,0		4,41	5,88
122,0		4,48	5,98
123,0		4,52	6,03
124,0		4,56	6,07
125,0		4,59	6,12
127,0		4,67	6,22
129,0		4,74	6,32
130,0		4,78	6,37
132,0		4,85	6,47
133,0		4,89	6,51
134,0		4,92	6,56
136,0		5,00	6,66
138,0		5,07	6,76
139,0		5,11	6,81
<b>140,0</b>		<b>5,14</b>	6,86
143,0		5,25	7,00
145,0		5,33	7,10
150,0		5,51	7,35
152,0		5,58	7,45
153,0		5,62	7,49

\* The diameter has to be measured at 150mm from the edge.  
*Il diametro deve essere misurato a 150 mm dalla estremità.*

 The quality normally used and available in stock.  
*Qualità generalmente utilizzate e disponibili a magazzino.*